

Microchip

Picosecond - Nanosecond Pulsed Laser

[L*]ProCareLight

Light, Laser and Safety Solutions



Features

Down to 400 ps

1064, 532, 355, 266 nm

946, 473, 236.5 nm

up to 60 kW peak power

up to 100 kW

up to 100 μ J

$M^2 < 1.3$



Applications

OLED

Micromachining

Biophotonics

LIDAR

Telemetry




Laser manufacturing

Non-linear optics

Spectroscopy



Raman

Holography



Microchip Lasers

	Microchip models		
	Nanoseconds		Picoseconds
Pulsewidth ranges	< 2 ns	< 1.5 ns	< 400 ps
Pulse energy	up to 35 μJ	up to 100 μJ	up to 2 μJ
Repetition rate	up to 10 kHz (internal and external trigger)	up to 15 kHz (internal and external trigger)	up to 100 kHz (internal and external trigger)
Peak power	up to 20 kW	up to 60 kW	up to 5 kW
Package	SB1		
Output wavelengths	946, 473, 236.5 nm	1064, 532, 355, 266 nm	
Beam Quality (M ²)	< 1.3		
Size	54 x 65 x 28 mm ³		
Weight	< 200 g		
Electrical requirements	12 V DC		
Operating temperature	+10° to +40° C		



OPTIONS AVAILABLE:

Monitoring photodiode

Beam Expanding and Collimating optics

Development kit

Heat-Sink

Quick start kit

Custom packaging